

© CrommelinWaterproofing

How to fix leaking gutters



CROMMELIN EXTERIOR GRADE BRUSHABLE WATERPROOFER is water based and quick drying. Suitable for use in areas such as gutters, roofs, flashings etc.

How to fix leaking gutters

EXTERIOR GRADE BRUSHABLE WATERPROOFER is a tough, flexible patching material and protective coating that will provide long term waterproofing protection.




YOU WILL NEED

1 litre of EXTERIOR GRADE BRUSHABLE WATERPROOFER will seal approximately 1.5m².



EQUIPMENT

EXTERIOR GRADE BRUSHABLE WATERPROOFER is easily applied by brush.



NUMBER OF COATS

2 coats are required and should be applied at 90° to each other.



DRYING TIME

Allow 2 hours drying time between coats.
Keep the surface dry for 24 hours before exposing to water or rain.



CLEAN UP

EXTERIOR GRADE BRUSHABLE WATERPROOFER is easily cleaned up with water before it dries.



TIPS

Any areas of pinholing or rust damage should be reinforced using REINFORCING BANDAGE between coats of EXTERIOR GRADE BRUSHABLE WATERPROOFER.

For detailed instructions on suitability, surface preparation and application steps, please refer to the product label.

Should you have any project specific questions or require further product information please do not hesitate to contact us.

Freecall Technical Advice 7 days: 1800 655 711
www.crommelin.com.au

Crommelin
Waterproofing & Sealing



Customers need to undertake their own assessment to determine the suitability of a product for the particular use intended. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it perform on the specific surface.