

© Crommelin Sealers



How to seal concrete floors & provide a decorative finish



CROMMELIN CONCRETE FLOOR SEALER

is water based and quick drying. An effective and economical treatment prior to, or as an alternative to, carpets, tiles or other floor coverings.

How to seal concrete floors & provide a decorative finish

A revolutionary clear finish used to transform plain concrete into an attractive yet cost effective dust-free floor.



YOU WILL NEED

4 litres of CONCRETE FLOOR SEALER will treat approximately 20m² of concrete floor.



EQUIPMENT

Either a roller or lambswool applicator can be used to achieve the desired finish.



NUMBER OF COATS

2 coats are required to give a dustproof and hardwearing decorative finish to your floor.



DRYING TIME

Allow 30 minutes between coats.

Leave the floor for 4 hours to cure before replacing your furniture.



CLEAN UP

CONCRETE FLOOR SEALER is easily cleaned up with water before the product dries.



TIPS

Apply to a dry surface. To test for moisture, tape down a clear plastic sheet over a small section of the surface to be treated in direct sunlight and leave for 2 hours. If moisture appears on the underside of the sheet the area is too damp.

For detailed instructions on suitability, surface preparation and application steps, please refer to the product label.

Should you have any project specific questions or require further product information please do not hesitate to contact us.

Freecall Technical Advice 7 days: 1800 655 711
www.crommelin.com.au

Crommelin
Waterproofing & Sealing



Customers need to undertake their own assessment to determine the suitability of a product for the particular use intended. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it perform on the specific surface.