

© CrommelinSealers

How to seal & protect pavers



CROMMELIN CONCRETE PAVING SEALER, WATER BASED PAVING SEALER, WETLOOK PAVING SEALER & POOL PAVING SEALER

provide durable and long lasting protection to a wide variety of paving and stencilled/patterned concrete surfaces.

How to seal & protect pavers

Ideal for all your paving sealing requirements, the Crommelin range of sealers will resist staining and protect your pavers to keep them looking like new.



YOU WILL NEED

1 litre of each of these products will cover approximately 3-5m² depending on the porosity of the paved area.



EQUIPMENT

These products are easily applied by brush, roller or spray.



NUMBER OF COATS

2 coats are required to give a good stain and water repellent seal to paved surfaces.



DRYING TIME

Allow 2-4 hours between coats.
Allow 6-8 hours before light foot traffic.



CLEAN UP

Please refer to the specific product label for the most effective method of clean up.



TIPS

Apply to a dry surface. To test for moisture, tape down a clear plastic sheet over a small section of the surface to be treated in direct sunlight and leave for 2 hours. If moisture appears on the underside of the sheet the area is too damp.

For detailed instructions on suitability, surface preparation and application steps, please refer to the product label.

Should you have any project specific questions or require further product information please do not hesitate to contact us.

Freecall Technical Advice 7 days: 1800 655 711
www.crommelin.com.au

© Crommelin
Waterproofing & Sealing



Customers need to undertake their own assessment to determine the suitability of a product for the particular use intended. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it perform on the specific surface.