

© CrommelinWaterproofing

How to waterproof retaining walls & planter boxes



CROMMELIN WATER BASED BITUMEN PAINT
is a heavy duty effective and economical solution for
waterproofing retaining walls, planter boxes and
other areas.

How to waterproof retaining walls & planter boxes

WATER BASED BITUMEN PAINT is a tough, flexible waterproof barrier which is both easy to use and safe for the environment.



YOU WILL NEED

1 litre of WATER BASED BITUMEN PAINT will cover approximately 0.75m² of wall area.



EQUIPMENT

WATER BASED BITUMEN PAINT is best applied by brush.



NUMBER OF COATS

2 coats are required and should be applied at 90° to each other.



DRYING TIME

Allow 30 minutes between coats.

Allow 7 days to fully cure before back filling.



CLEAN UP

WATER BASED BITUMEN PAINT is easily cleaned up with water before it dries. If it is difficult to remove or clean use mineral turps.



TIPS

Apply to a dry surface. To test for moisture, tape down a clear plastic sheet over a small section of the surface to be treated in direct sunlight and leave for 2 hours. If moisture appears on the underside of the sheet the area is too damp.

For detailed instructions on suitability, surface preparation and application steps, please refer to the product label.

Should you have any project specific questions or require further product information please do not hesitate to contact us.

Freecall Technical Advice 7 days: 1800 655 711
www.crommelin.com.au

Crommelin
Waterproofing & Sealing



Customers need to undertake their own assessment to determine the suitability of a product for the particular use intended. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it perform on the specific surface.