

© Crommelin Waterproofing



How to weatherproof brick walls & other surfaces

CROMMELIN NATURAL FINISH SEALER is a quick drying, durable and effective sealer to protect against water penetration on a variety of substrates.

How to weatherproof brick walls & other surfaces

NATURAL FINISH SEALER provides a matt finish water repellent seal to most porous surfaces including concrete, pavers, timber and canvas.



YOU WILL NEED

1 litre of NATURAL FINISH SEALER will seal approximately 3-5m² depending on the surface.



EQUIPMENT

NATURAL FINISH SEALER is easily applied by brush, roller or spray.



NUMBER OF COATS

2 coats of NATURAL FINISH SEALER is all you need to seal and protect most surfaces.



DRYING TIME

Allow 30 minutes drying time between coats.
Leave for 2 hours before you put the surface in use.



CLEAN UP

NATURAL FINISH SEALER can be cleaned with CROMMELIN CLEANING & THINNING SOLVENT or mineral turps immediately after use.



TIPS

Apply to a dry surface. To test for moisture, tape down a clear plastic sheet over a small section of the surface to be treated in direct sunlight and leave for 2 hours. If moisture appears on the underside of the sheet the area is too damp.

For detailed instructions on suitability, surface preparation and application steps, please refer to the product label.

Should you have any project specific questions or require further product information please do not hesitate to contact us.

Freecall Technical Advice 7 days: 1800 655 711
www.crommelin.com.au

 **Crommelin**
Waterproofing & Sealing



Customers need to undertake their own assessment to determine the suitability of a product for the particular use intended. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it perform on the specific surface.