

# Technical Data Sheet

## Rocfloor®

Flooring

7 Day Technical Support 1800 655 711

Testing Approvals: N/A

### Description

Rocfloor® is a waterborne sealer, hardener and dustproofer for new or old concrete floors. It is a proven and highly effective means of providing a durable and stain resistant finish. The unique combinations of physical and antimicrobial properties ensure Rocfloor® is not only hygienic but also suitable for both commercial and industrial floors. VOC content of Rocfloor® is below the maximum VOC content for interior sealers as required by Green Star Design V2, V3, Office Interiors V.1.1

### Features and Benefits

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• Prevents dusting and deterioration of concrete surfaces</li> <li>• Excellent stain resistance</li> <li>• Outstanding adhesion</li> <li>• High abrasion resistance</li> <li>• Surface hardening</li> <li>• Waterborne and non-toxic</li> <li>• Low sheen finish</li> </ul> | <ul style="list-style-type: none"> <li>• Antimicrobial incorporation assists in easy cleaning</li> <li>• Quick drying – 2 coats applied in one day</li> <li>• Very low V.O.C's. and low odour – safe interior use</li> <li>• No involved clean-up required after application, as with common surface hardeners</li> <li>• Can be over coated with suitable paints adhesives and floor coverings</li> <li>• Excellent resistance to mild acids and alkalis</li> </ul> |
|--|--|

### Areas of Use

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>• Warehouses floors</li> <li>• Factory floors</li> <li>• Commercial floor areas</li> </ul> | <ul style="list-style-type: none"> <li>• Loading docks</li> <li>• Tilt up panels</li> <li>• Concrete walls</li> </ul> |
|---|---|

### Technical Data

Number of Coats:	2	Recoat (@25°C):	2-4 hrs
Spreading Rate Per Coat		Curing time:	7 Days
New Concrete:	10m <sup>2</sup> /L	Colour:	Milky, dries clear
Old/Dusting Concrete:	6-8m <sup>2</sup> /L	Thinner:	Water
Wet Film Per Coat:	75-110 microns	Shelf Life:	12 months

Properties	Test Method	Test Results
Volatile Organic Compound (VOC) Content	SCAQMD 304-91	63.7g/L

# Technical Data Sheet

## Rocfloor®

Flooring

7 Day Technical Support 1800 655 711

### Application Guide

#### Surface Preparation

- For new concrete, ensure concrete has been cured for at least 28 days. Ensure all traces of oil or other contaminants are removed, as this may affect adhesion.

For old concrete, remove all contaminants by mechanical or chemical means, such as detergent wash, household bleach and high-pressure washing. The level of cleaning will determine the final appearance that will be achieved.

#### Application Procedure and Equipment

- Before application, assess the porosity of the concrete. If the concrete has little or no porosity, dilute Rocfloor® 2:1 with water and apply this diluted mixture at a rate of 10m<sup>2</sup> / L. This will assist in good penetration.
- If the first coat imparts a well-sealed surface, to prevent a high gloss finish, dilute the second coat 2:1 with water as well, and apply at a rate of 10m<sup>2</sup> / L. If a high gloss finish is required the second coat may be applied undiluted.
- For older, worn/dusting concrete, dilution is not required.

### Precautions

- Do not apply Rocfloor® if the temperature is below 10°C, or if relative humidity is above 85% or if rain is imminent.
- Do not apply Rocfloor® to wet substrates – moisture content should be less than 15%. Check with a moisture meter.

### Cleaning

- All equipment can be cleaned with water before it dries.

### Health and Safety

#### Safety Precautions

- Provide good ventilation – open windows and doors and use circulating fans.
- If product is splashed on skin it should be washed off with water before it can dry.
- Wear gloves and eye protection during application.

#### First Aid

Swallowed: Contact a doctor or Poisons Information Centre. Do not induce vomiting. Give water to drink.

Eye: Gently flush with running water, holding eyelids open for 15 minutes. Seek medical attention.

For detailed information refer to product label and the current Material Safety Data Sheet available from Crommelin®.

In the case of an emergency please call the Poisons Information Centre on 13 11 26

# Technical Data Sheet

## Rocfloor®

Flooring

7 Day Technical Support 1800 655 711

### Transport and Storage

Sizes:	15L, 200L	Flash Point:	43°C
Weights:	15.5Kg, 210Kg	UN Number:	N/A
Dangerous Goods Class	N/A		

### Disclaimer

Crommelin® and other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks. Any advice, recommendation, information, assistance or service provided by Crommelin® in relation to its products or their use is given in good faith, however is provided without responsibility or liability. Customers need to undertake their own assessment to determine the suitability of a product for the particular use intended. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.