



Next Day SB

Green concrete sealer and screed efflorescence suppressant.

DESCRIPTION

Next Day SB is a solvent based clear coating, formulated for use on both green and existing concrete surfaces.

Next Day SB provides immediate protection from staining, dirt and water damage, whilst delivering a subtle wet look and good substrate colour enhancement.

Next Day SB is also highly resistant to the upward movement of calcium containing moisture, providing effective rising efflorescence suppression when applied to the surface of screeds.

ADVANTAGES

Next Day SB delivers the following advantages;

- Satin “wet look” to gloss finish.
- Suitable for application to concrete surfaces after 24 hours.
- Good surface protection from stains, dirt and water damage.
- Clear, non-yellowing formula.
- Single coat application.
- Good substrate colour enhancement.
- Assists concrete curing process.
- Effective screed efflorescence suppressant.
- Excellent substrate adhesion.
- Interior and exterior application.
- High UV resistance.
- Suitable for use in conjunction with all cementitious tile adhesives that conform to AS2358.

AREAS OF USE

Next Day SB is suitable for use in the following areas;

- Walkways & Driveways
- Warehouses
- Previously Uncoated Concrete
- Pedestrian Areas
- Under Tile Screeds

Note: Next Day SB is not suitable or recommended for use on natural stone, clay pavers, timber, poorly consolidated, weak, friable and dusty substrates or Fremantle Stone products.

SUBSTRATES

Next Day SB is suitable for application on;

- Green Concrete
- Existing Concrete
- Patterned Concrete
- Stencilled Concrete
- Under Tile Screeds

TECHNICAL DATA (@ 25°C)

Number of Coats:	1
Coverage: (per coat)	6 - 10m ² /L
Wet Film: (per coat)	100 – 150 microns
Recoat:	2 hours (if required)
Foot Traffic/Tile Over:	24 hours
Full Cure:	7 days
Colour:	Clear
Clean Up:	Crommelin Solvent
Shelf Life:	12 months

Next Day SB

Green concrete sealer and screed efflorescence suppressant.

ANCILLARY PRODUCTS

- Crommelin® Contractor Membrane Applicator Brush – 100mm, 75mm
- Crommelin® Contractor Membrane Roller Cover – 230mm
- Crommelin® Moisture Meter

SUBSTRATE PREPARATION AND PRIMING

Full substrate preparation instructions can be found at www.crommelin.com.au/full-instructions/

Surfaces must be clean, sound and free from dust, grease, curing compounds, release agents, loose particles, efflorescence, concrete laitance or any other contaminants.

Green Concrete

- New concrete should be allowed to cure for a minimum of 24 hours before application. Surfaces must be cured sufficiently to walk on.

Existing Concrete

- If acid etching has taken place, ensure neutralisation of the area and thorough rinsing has been conducted.
- If area has been previously sealed, ensure coating compatibility. If in doubt, remove existing coating.
- If area has been previously sealed, ensure re-coating will not produce an excessive film build that may compromise the breathability of the substrate.

Screed Efflorescence Suppression

- New screeds should be allowed to cure for 24 hours.

APPLICATION CONDITIONS

- Substrate must be dry. The use of suitable moisture meter is recommended.
- Application temperature must be above dew point.
- Do not apply if relative humidity is above 85% during initial cure phases, or if rain is expected before cure.

Note: When applying internally or in humid conditions, air flow should be maximised with the use of fans to assist cure.

APPLICATION

Full application instructions can be found at www.crommelin.com.au/full-instructions/

- Apply a trial patch before full application, to assess sealer adhesion, substrate colour enhancement, gloss level and slip resistance.
- Test surface for porosity before full application to ensure that surface sealing is required.
- Apply Next Day SB with Crommelin® Contractor Membrane Brush, Crommelin® Contractor Membrane Roller or airless spray at a pressure of 800 – 1000 p.s.i.
- Colour enhancement level and uniformity of sheen will be determined by substrate porosity.
- Protect sealed area from light foot traffic for at least 24 hours.
- Do not park vehicles on sealed area for at least 7 days.
- When applying on green concrete, once substrate has fully cured (28 days), apply Crommelin® Enhance Gloss or Crommelin® Enhance Satin for long term protection.

Important note: When applying on screeds to suppress rising efflorescence, ensure that the entire area is well coated and no areas are missed.

CLEAN UP

- Equipment can be cleaned with Crommelin® solvent of similar.



Next Day SB

Green concrete sealer and screed efflorescence suppressant.

MAINTENANCE, RECOATING AND REPAIR

To maximise the natural life and protective characteristics of your sealer general cleaning and maintenance should be followed including;

- Any spills must be cleaned up immediately. Spot cleaning should be carried out with dilute detergents.
- It is recommended that areas treated be scrubbed or mechanically cleaned monthly using appropriate cleaning fluids.
- The placement of mats at all entry and exit points is recommended.
- Repair damage by ensuring the area is clean and dry and re-apply sealer as per recommended coverage rates.
- Re-coating should only take place as required to maintain the greatest level of performance.
- When re-coating, ensure sealer compatibility and ensure that excessive film build is not produced.

PRECAUTIONS

- Do not apply if the temperature is below 7°C, below dew point or relative humidity is above 85% or if rain is imminent.
- Ensure adequate ventilation and air flow to optimise membrane curing.

WARRANTIES

Please contact your Crommelin® representative, or the Crommelin® technical support team for detailed specifications applicable to your project and warranty requirements.

Crommelin® and other marks followed by ® are registered trademarks.

Any advice, recommendation, information, assistance or service provided by Crommelin® in relation to its products or their use is given in good faith, however is provided without responsibility or liability.

Customers need to undertake their own assessment to determine the suitability of a product for the intended use. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs as required on the specific surface.

Crommelin® also reserves the right to update information without prior notice, to reflect ongoing research and product development.

TRANSPORT AND STORAGE

- Size: 15L
- Weight: 15kg
- DG Class: 3
- Flash Point: 43°C
- UN Number: 1263
- Cool and Dry Storage
- Hazchem Code: 3(Y)
- Poison Schedule: 5

SAFETY AND FIRST AID

Next Day SB Safety Data Sheet is available from Crommelin® upon request.

Safety

- Ensure good ventilation and avoid breathing vapours.
- Avoid skin and eye contact. Wear gloves and eye protection. Remove splashes on skin immediately and remove contaminated clothing.
- Keep out of reach of children.
- Keep container sealed when not in use.
- Do not swallow.

First Aid

- If poisoning occurs, contact a doctor or poisons information centre: Ph. 13 11 26.
- If swallowed, do not induce vomiting. Give a glass of water to drink.
- If in eyes, hold eyes open and flood with water for at least 15 minutes.
- If not breathing, apply artificial respiration.



7 Day Technical Support 1800 655 711

72 Division Street, Welshpool Western Australia 6106 T +61 8 9458 5711 F +61 8 9451 4749
service@crommelin.com.au www.crommelin.com.au