

# CROMSEAL™

## Fibro Seal® Primer

Testing Approvals: APAS GPC-C-172/2 encapsulation system for asbestos sheeting.

### Description

CROMSEAL™ Fibro Seal® Primer is a waterborne penetrating treatment to weathered asbestos cement sheeting that soaks through the lichen and degraded asbestos down to sound base material, binding these unstable elements. When used together with CROMSEAL™ Fibro Seal® Topcoat, the product forms part of the CROMSEAL™ Fibro Seal® System, a proven encapsulation system used throughout Australia since 1990.

### Features and Benefits

- Bind weathered asbestos cement sheet fibres
- Waterborne

### Areas of Use

- Weathered asbestos cement products

### Technical Data

Number of Coats:	1	Curing time:	7 days
Spreading Rate Per Coat:	3m <sup>2</sup> /L	Colour:	Clear
Wet Film Per Coat:	330 microns	Thinner:	N/A
Recoat (@25°C):	2 hours	Shelf Life:	12 months

### Application Guide

#### Surface Preparation

- Remove large lumps of lichen and moss growth manually and clean loose growth away with an industrial vacuum cleaner.
- Assess the degree of weathering of the asbestos fibres by applying a length of self adhesive tape to the surface. Adhere completely and then pull off in one swift motion. Use this as the basis for assessing the effectiveness of the CROMSEAL™ Fibro Seal® Primer.

#### Application Procedure and Equipment

- Apply the specified flood coat of CROMSEAL™ Fibro Seal® Primer using spray, brush or roller.
- Reassess the complete binding of the asbestos fibres by the CROMSEAL™ Fibro Seal® Primer using a self adhesive tape "pull off test". If fibres appear on the adhesive surface apply a 2<sup>nd</sup> coat. Reassess.

### Precautions

- Ensure all requirements applicable to the relevant state Occupational Health and Safety legislation are complied with.
- When working on weathered asbestos roofs, refer to NOHSC Codes of Practice 2018 (2005) Management and Control of Asbestos in Workplaces.

### Cleaning

- Clean equipment with water before product dries.

# CROMSEAL™

## Fibro Seal® Primer

Testing Approvals: APAS GPC-C-172/2 encapsulation system for asbestos sheeting.

### Health & Safety

#### Safety Precautions

- Avoid contact with skin and eyes.
- If product is splashed on skin it should be washed off with water before it can dry.
- Wear suitable protective clothing, gloves and eye protection during application.

#### First Aid

Swallowed: Contact a doctor or Poisons Information Centre. Do not induce vomiting. Give water to drink.  
 Eye: Gently flush with running water, holding eyelids open for 15 mins. Seek medical attention.

For detailed information refer to product label and the current Material Safety Data Sheet available from Crommelin.

In the case of an emergency please call the Poisons Information Centre on 13 11 26

### Transport & Storage

Sizes:	20L	Flash Point:	N/A
Weights:	22Kg	UN Number:	N/A
Dangerous Goods Class:	N/A	Poisons Schedule:	5

### Disclaimer

Crommelin and other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

Any advice, recommendation, information, assistance or service provided by Crommelin in relation to its products or their use is given in good faith, however is provided without responsibility or liability. Customers are advised to undertake their own assessment to determine suitability of a product for the particular use intended. Due to the performance of any product being subject to a wide variety of field and surface conditions we are unable to assume liability for any loss, consequential or otherwise that may arise from the use of our products. Where a product is proven defective, our liability is limited to the replacement of the product.