



How to weatherproof brick walls & other surfaces

CROMMELIN NATURAL FINISH SEALER is a quick drying, durable and effective sealer to protect against water penetration on a variety of substrates.

How to weatherproof brick walls & other surfaces

NATURAL FINISH SEALER provides a matt finish water repellent seal to most porous surfaces including concrete, pavers, timber and canvas.



YOU WILL NEED

1 litre of NATURAL FINISH SEALER will seal approximately 6m² depending on the surface.



EQUIPMENT

NATURAL FINISH SEALER is easily applied by brush, roller or spray.



NUMBER OF COATS

2 coats of NATURAL FINISH SEALER is all you need to seal and protect most surfaces.



DRYING TIME

Allow 30 minutes drying time between coats.
Leave for 2 hours before you put the surface in use.



CLEAN UP

NATURAL FINISH SEALER can be cleaned with CROMMELIN CLEANING & THINNING SOLVENT or mineral turps immediately after use.



TIPS

Apply to a dry surface. To test for moisture, tape down a clear plastic sheet over a small section of the surface to be treated in direct sunlight and leave for 2 hours. If moisture appears on the underside of the sheet the area is too damp.

For detailed instructions on suitability, surface preparation and application steps, please refer to the product label.

Should you have any project specific questions or require further product information please do not hesitate to contact us.

Freecall Technical Advice 7 days: 1800 655 711
www.crommelin.com.au

Crommelin
SOLUTIONS FOR CONSTRUCTION



Customers are advised to undertake their own assessment to determine suitability of a product for the particular use intended. Due to the performance of any product being subject to a wide variety of field and surface conditions we are unable to assume liability for any loss, consequential or otherwise that may arise from the use of our products. Where a product is proven defective, our liability is limited to the replacement of the product.