

Project Guide

1. Surface Type & Preparation

- Non-porous surfaces should be sanded to provide a mechanical "key"
- Porous surfaces should be sealed with LiquidStone Surface Primer
- All surfaces must be completely dry and dust free
- Mould and algal growth must be removed with a mild bleach solution and rinsed with clean water
- Remove oil, tyre marks and surface contaminants with DiamondCoat Paving Cleaner

3. Protection

- Protect you surface with LiquidStone Clear Coat
- Provides a tough, semi gloss finish Coat

2. Application

- Prior to coating, a trial area should be completed in an inconspicuous area to assess coating and surface compatibility
- Stir chosen LiquidStone colour thoroughly before use
- Apply LiquidStone with a brush or medium nap roller
- For full preparation and application details, refer to product labels

4. Clean Up & Disposal

- Clean uncured material from application equipment by washing in warm water
- Dispose of unused material in accordance with local authority regulations



Surface Primer



Clear Coat

LiquidStone Pattern Tape

LiquidStone Pattern Tape is a filament reinforced tape designed to create stencilled patterns on small areas of concrete with LiquidStone colours

- Suitable surfaces – concrete, fibre cement cladding, garden ornaments
- Areas of use – walkways, paths, courtyards, facades and walls
- Surface preparation – Prime porous surfaces with LiquidStone Surface Primer and ensure that all surfaces are completely dry and free from dirt, dust, algal growth, oil and other contaminants

To create a uniform and consistent pattern, always ensure the following:

- Measurement – pattern is measured out and partially marked using a pencil or chalk
- Tape application – tape should be applied in a progressive manner, ensuring that all edges are firmly adhered
- Tape removal – tape should be removed immediately after application of the second LiquidStone coat and before it dries, to ensure a clean edge is obtained



Pattern Tape

