

SADOLIN Hardwood Oil

Premium oil-based hardwood oil for garden furniture and decks with excellent penetration and water repellency to protect and enhance the natural beauty of timber.



Enhances the natural beauty of timber
Easy to apply
Excellent penetration and water repellency
Weather resistant

Product Description: Sadolin Hardwood Oil is a high-quality hardwood oil formulated to penetrate deeply into most timber species and provide excellent protection against the elements. Sadolin Hardwood Oil is water repellent and particularly suitable for exterior hardwood surfaces where a natural appearance is required.

Sadolin Hardwood Oil is recommended for timber garden furniture and decks.

Product Range: Colourless Teak Natural

Preparation: Sadolin Hardwood Oil is recommended for use on bare timber or on timber that has previously been treated with similar timber care products that produce no film on the surface e.g. preservative pre-treatments or oils.

Ensure that the timber is clean, dry and free from grease.

New or unseasoned hardwood such as Merbau (Kwila), Spotted Gum, Tallowwood, Jarrah and Ironbark contain natural tannins. These tannins need to be extracted prior to coating. This will happen naturally over a period of 3-6 months depending on exposure, or the process can be accelerated using Sikkens Cetol® Tannin & Oil Remover followed by Sikkens Cetol® Deck & Wood Cleaner.

New tannin-rich timbers:

Apply Sikkens Cetol® Tannin & Oil Remover according to on-pack instructions, allow to sit on the timber surface for 15 minutes before thoroughly rinsing with a pressure washer or hose. Whilst timber remains wet, apply a liberal coat of Sikkens Cetol® BL Deck & Wood Cleaner and scrub into the surface: leave for 15 minutes then thoroughly rinse with pressure washer or hose. Allow to dry completely prior to application.

New timbers with no tannin content or previously oil-treated aging timbers:

Wet the timber and apply Sikkens Cetol® BL Deck & Wood Cleaner or a similar solution for surface cleaning and rinse thoroughly. Allow to dry completely prior to application.

Previously coated timber with an intact or damaged film:

Sand back to bare timber, remove any old product or residue.

Non-durable exterior timbers (e.g. Pine) should receive a preservative pre-treatment prior to the application of Sadolin Hardwood Oil. Preservative pre-treatments must be fully dried before the application of Sadolin Hardwood Oil.

Application: Stir well before and during application and apply by brush or cloth. Do not apply at temperatures below 5°C. Do not thin.

Apply one coat of Sadolin Hardwood Oil and allow it to dry for 5 to 30 minutes depending on the temperature and humidity. Remove any residues of Sadolin Hardwood Oil, which have not been absorbed, by gently wiping with a cloth. This will help to prevent “glossy” blemishes on the surface.

FURTHER SUPPORT

If you need further support, please contact Crommelin on 1800 655 711 – 7 days.
Crommelin is an authorised distributor of Sikkens Cetol and Sadolin Timber Finishes in Australia.
Always read full Health, Safety & Environmental Information on can before use.

For maximum durability, apply 2 to 3 coats of Sadolin Hardwood Oil. The colourless version is less durable than the coloured version. It is recommended that at least one coat of Sadolin Hardwood Oil is applied every year.

- Coverage:** Approximately 15-18 m²/litre on smooth wood.
- Drying Time:** Touch dry: 4-6 hours.
Repainting: Subsequent coats can be applied after 12-24 hours.
- Cleaning:** Clean the brushes or rollers immediately after use in white spirit.
- Important Information:** Protect from frost.
Shelf life: (Unopened) at least 5 years from production date.
Please refer to the Technical Data Sheet for detailed information.



2020

FURTHER SUPPORT

If you need further support, please contact Crommelin on 1800 655 711 – 7 days.
Crommelin is an authorised distributor of Sikkens Cetol and Sadolin Timber Finishes in Australia.
Always read full Health, Safety & Environmental Information on can before use.