

Gecko[®] Colour Tints

Universal colour tints for Gecko[®] Epoxyflex and Polyurethane coatings.

DESCRIPTION

Gecko[®] Colour Tints are a range of colour tint packs formulated for use with Gecko[®] Epoxyflex and Polyurethane topcoats.

Gecko[®] Colour Tints will deliver full colour opacity when applied as part of the chosen topcoat system.

ADVANTAGES

Gecko[®] Colour Tints deliver the following advantages:

- Universal tint system for Gecko[®] Epoxyflex and Polyurethane topcoats.
- Easy mixing.
- Simple mix ratios.
- Full cover opacity.
- 10 standard colour options.
- Custom colours available upon request for large volume projects.

AREAS OF USE

Gecko[®] Colour Tints are suitable for use in the following areas:

- Gecko[®] Primers
- Gecko[®] Epoxyflex Topcoats
- Gecko[®] Polyurethane Topcoats

PRODUCT PREPARATION

- Only add full tint packs.
- Tint pack colour mixing is not recommended.
- Mix tint packs separately to ensure full pigment dispersion before adding to pre-mixed Gecko[®] topcoat.
- Add all of the required tint to pre-mixed topcoats kits, scraping the can to make sure that no material is left unmixed.
- Mix thoroughly, using a slow speed drill and spiral mixing paddle, at a maximum of 500 rpm, to produce a homogenous colour mix. Avoid air entrapment.

COLOURS & ADDITION RATES

Colour		8L Kit	16L Kit
Light Grey		500ml	1L
Mid Grey		500ml	1L
Dark Grey		500ml	1L
Koala Grey	AS2700-N45	500ml	1L
Black		500ml	1L
White		500ml	1L
Yellow		500ml	1L
Red		500ml	1L
Green		500ml	1L
Blue		500ml	1L
Custom Colours	Refer to your Crommelin rep for advice		

CLEAN UP

- Uncured material may be removed with Xylene.
- Cured material may be removed mechanically.

PRECAUTIONS

- Gecko[®] Epoxy products are not UV stable and will yellow or colour fade with UV exposure.
- For exterior applications, refer to Gecko[®] Polyurethane Systems.
- A test patch is recommended prior to full application to assess colour suitability, coating adhesion and slip-resistive finish.
- Final slip-resistive rating is determined by substrate profile and application rate. Slip-resistive ratings may only be achieved by measurement on site.

Gecko[®] Colour Tints

Universal colour tints for Gecko[®] Epoxyflex and Polyurethane coatings.

TRANSPORT AND STORAGE

- Refer to SDS for DG information
- Cool and dry storage
- Size & Weight:

Colour	Size	Weight:
Light Grey	500ml	1KG
Mid Grey	500ml	1KG
Dark Grey	500ml	1KG
Koala Grey	500ml	1KG
Black	500ml	1KG
White	500ml	1KG
Yellow	500ml	0.95KG
Red	500ml	0.6KG
Green	500ml	1KG
Blue	500ml	0.95KG

SAFETY AND FIRST AID

Gecko[®] Colour Tints Safety Data Sheet is available from Crommelin[®] upon request.

Safety

- Ensure good ventilation and avoid breathing vapours.
- Avoid skin and eye contact. Wear gloves and eye protection. Remove splashes on skin immediately and remove contaminated clothing.
- Keep out of reach of children.
- Keep container sealed when not in use.
- Do not swallow.

First Aid

- If poisoning occurs, contact a doctor or poisons information centre: Ph. 13 11 26.
- If swallowed, do not induce vomiting. Give a glass of water to drink.
- If in eyes, hold eyes open and flood with water for at least 15 minutes.
- If not breathing, apply artificial respiration.

Crommelin[®], Gecko[®] and other marks followed by ® are registered trademarks.

Any advice, recommendation, information, assistance or service provided by Crommelin[®] in relation to its products or their use is given in good faith, however is provided without responsibility or liability.

Customers need to undertake their own assessment to determine the suitability of a product for the intended use. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs as required on the specific surface.

Crommelin[®] also reserves the right to update information without prior notice, to reflect ongoing research and product development.