



Application	Rapid Repair Filler	Light & Smooth Super Filler	Flexible Wood Filler	Universal Fine Filler	Super Exterior Filler
Interior Use	Yes	Yes	Yes	Yes	Yes
Exterior Use	Yes	Yes	Yes	No	Yes
Timber Use	Yes	Yes	Yes, ideal for staining, varnishing & painting	Yes, high gloss result	Yes
Single Application Filling Depth	5mm	50mm (max 100mm in two layers)	10mm (max 20mm in two layers)	2mm	50mm (max 100mm in two layers)
Drying Time	Touch dry (2mm fill) in 2min. Sand & paint after 15 minutes (5mm fill) with all types of paint.	Touch dry in 20min. Sand & paint after 3.5 hours (2mm fill) & 24 hours (5cm fill). Paint without sanding from 2 hours (5cm fill). For oil based paints wait 24 hours.	Sand & paint after 1 hour (2mm fill) or 3 hours (10mm fill) with all types of paint, varnishes or stains.	Sand & paint after 4 hours with all types of paints.	Sand and paint after 3.5 hours (2mm fill) & 24 hours (5cm fill). Paint without sanding from 3 hours (5cm fill). Oil-based paints wait 24 hours.
Finish	Smooth, white	Super smooth, white	Smooth, natural/pine	Super smooth, white	Slightly coarse, light grey
Sandability	Easy to sand	No need to sand	Easy to sand	Easy to sand	Easy to sand
Nail/Screw Acceptance	Yes	No	Yes	No	Yes, also drillable