

Technical Data Sheet

UNIVERSAL FINE FILLER



APPLICATIONS

- For use on interior walls and joinery, including doors, windows, trim, architraves and skirting boards
- Fill fine cracks up to 2mm, minor blemishes or wood grain for a professional, glass smooth surface for painting

PRODUCT PROPERTIES

- Ready to use
- Sand & paint after 4 hours (2mm fill at 20°C) with all types of paint
- Super smooth white finish
- Easy to sand
- Maximum depth: 2 mm
- Particle size: Max 0.10 mm

INSTRUCTIONS FOR USE

- Substrate and crack must be clean, dry and free from loose material.
- New wood should be primed first.
- Rub down gloss surfaces for improved adhesion.
- Metal surfaces such as nails and screws should be treated with an appropriate rust resistant primer.
- Apply with a filling knife and spread over the surface, pressing in well.
- Remove any excess filler and leave to dry.
- For an even smoother finish rub down with sand paper.
- Use appropriate protection when sanding.
- Do not apply when the surface temperature is below + 5°C.
- Replace lid after use.
- Wash tools with warm water.

PACK SIZES

330 gr – 1 L (1.8kg) Special Order – 2,5 L (4.4kg) Special Order

FURTHER SUPPORT

IF YOU NEED FURTHER SUPPORT, PLEASE CONTACT CROMMELIN ON 1800 655 711 – 7 DAYS. CROMMELIN IS AN AUTHORISED DISTRIBUTOR OF NORDSJÖ PROFESSIONAL FILLERS IN AUSTRALIA.

ALWAYS READ FULL HEALTH, SAFETY & ENVIRONMENTAL INFORMATION ON PACKAGING BEFORE USE.