



Waterproofing Tape

Flexible Self-Adhesive Joint Sealing Tape

DESCRIPTION

Crommelin Waterproofing Tape is a multipurpose, self-adhesive, interior and exterior, tear resistant, joint sealing tape for use prior to over-coating that delivers an instant seal.

FEATURES AND BENEFITS

- Quick and easy application.
- Excellent adhesion and instant waterproofing.
- Tough, durable and tear resistant.
- Over-coat with Crommelin waterproofing membranes, tile adhesives, renders, screeds and textured coatings.
- Use on metal, tiles, cement sheet, dense concrete, timber, plasterboard and other non-porous surfaces.
- 5m x 80mm roll.

AREAS OF USE

Waterproofing Tape is suitable for use in the following areas:

- Crack repairs on floors before tiling, screeds and toppings.
- Waterproofing junctions before tiling.
- Sealing floor sheeting joints.
- Detailing sheeting before rendering or textured coatings.
- Detailing pipes and penetrations.
- Patching pinholes and flashing.

APPLICATION PROCESS

Full application instructions can be found at www.crommelin.com.au/full-instructions/

- Ensure surface is clean, dry and contaminant free. If surfaces are dusty, prime with Crommelin Surface Primer for Porous Surfaces first. If surfaces are damp, prime with Crommelin Dampstop first. Metal surfaces must be rust free or treated with suitable primer.
- Measure out the length of tape required and cut with scissors or knife.
- Remove the end of the release paper and adhere the tape to the area to be sealed. For best results, slowly roll and stick tape along the length of the joint whilst removing release paper as you go. It is not recommended to remove all release paper before sticking tape to the surface.
- Ensure that no creases or air pockets form by pressing tape into position with a spatula or similar.
- Crommelin waterproofing membranes or other toppings can be applied immediately.

Note: Do not apply to damp surfaces. Not suitable for use as a trafficable surface or an exposed flashing. Must be over-coated. Do not use over expansion joints. Do not directly over-coat with solvent based coatings.

Product Information

Technical Data Sheet – November 2022

Crommelin[®]
Waterproofing & Sealing



SIZES

Waterproofing Tape is available in the following profiles;

- 5m x 80mm roll.

PRECAUTIONS

- Where **Waterproofing Tape** is used, drying times of waterproof membrane may be increased.

TRANSPORT AND STORAGE

- Weight: 0.93kg
- Cool and Dry Storage
- UN Number: N/A
- DG Class: N/A
- Flash Point: N/A
- Hazchem Code: N/A
- Poisons Schedule: N/A

Crommelin[®] and other marks followed by ® are registered trademarks.

Any advice, recommendation, information, assistance or service provided by Crommelin[®] in relation to its products or their use is given in good faith, however is provided without responsibility or liability. Customers need to undertake their own assessment to determine the suitability of a product for the intended use. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs as required on the specific surface.

Crommelin[®] also reserves the right to update information without prior notice, to reflect ongoing research and product development.

7 Day Technical Support 1800 655 711

72 Division Street, Welshpool Western Australia 6106 T +61 8 9458 5711 F +61 8 9451 4749
service@crommelin.com.au www.crommelin.com.au

Page 2 of 2