

sikkens

FOR THE BEST

1 POT SYSTEM

Durable Translucent Decking Finish with High UV Protection

Cetol Deck Ultra

Penetrates, seals, colours and covers decking with a protective translucent satin film.
2-in-1: self-priming.



RAW TIMBER

NATURAL

MERBAU



Natural & Translucent Decking Oil

Cetol BL Natural Decking Oil

Penetrates, seals, colours and covers decking with a subtle matt, protective translucent film.
Quick dry formula. Finish the job in a day.



RAW TIMBER

NATURAL

MERBAU



Preserving & Nourishing Deck & Timber Oil.

Cetol Premium Timber Oil

Penetrates, nourishes, seals and protects all exterior timber without a surface film.
Natural look. Matt finish.



RAW TIMBER

NATURAL

MERBAU



Quick & easy prep & application

Project	Preparation
New hardwood decking	Treat with Cetol® Tannin & Oil Remover before cleaning.
New softwood decking	Cleaning is all you need.
Previously oiled or stained decking	If water still beads on the surface - treat with Cetol® Tannin & Oil Remover before cleaning. If water is absorbed – cleaning is all you need.
Flaking, peeling & grey weathered deck	Sand the surface back to bare timber before cleaning.
General seasonal re-coating	Just a clean and allow to dry.

Cleaning & Application

Simple steps to follow before applying Cetol® timber coatings.

- Clean with Cetol® Deck & Wood Cleaner & allow to thoroughly dry.
- Lightly sand the surface & remove dust. Use 60 – 80 grit sandpaper for hardwood or 100 – 120 grit for softwood.
- Apply with a good quality brush, along the grain, taking care to coat nail holes and board ends well.

Product	Coverage
Cetol® Deck Ultra	Bare timber: 3 coats. Seasonal refresh: 1 coat. 10m ² per litre per coat. 24 hours between coats.
Cetol® BL Natural Decking Oil	Bare timber: 2-3 coats. Seasonal refresh: 1 coat. 12m ² per litre per coat. 2 hours between coats.
Cetol® Premium Timber Oil	Bare timber: 2 coats. Seasonal refresh: 1 coat. 8m ² per litre per coat. 24 hours between coats.

Want more Cetol® Deck Ultra colour options?

Cetol® Deck Ultra is available ready to use in Natural & Merbau.

For more colours simply apply one coat of Cetol® HLSe in your choice of colour followed by two coats of Cetol® Deck Ultra Natural for long term protection.



Find out more sikkens.com.au or scan QR code

sikkens

Still not sure?
7 day helpline 1800 655 711